

Item

WALK-IN COOLER W/DISPLAY DOORS

NOR-LAKE INC Model No. CUSTOM

Walk-In Cooler w/Display Doors - 7' 3-5/8" high floorless with 1" vinyl screeds, interior walls .040 embossed white aluminum, smooth white ceiling and, exterior walls .040 embossed aluminum. (2) 36" x 78" Entrance doors, 3rd hinge, 36" high kickplates interior/exterior doors only, digital thermometer, hydraulic door closer, chrome latch handle (deadbolt lock).

(1) Set of 6 Energy Door Company glass door 24" x 67" high w/flat 36" deep shelving.

AS PER NORLAKE QUOTE #NL2227957NNA

1 ea Singer Ashland CUSTOM Trim and Enclosure Panels

1 ea Singer Ashland Stand For Refrigeration Compressor

1 ea REFRIGERATION SYSTEM

NOR-LAKE INC Model No. RF0400E4SDANT

Refrigeration System w/Evaporator Coils- 4hp Med Temp Air Cooled Scroll Condensing Unit (2) Evaporator Coils Air Defrost Low Profile Coil (Unit Cooler) - included in pricing above.

3 ea UNDERBAR ADD-ON UNIT

Advance Tabco Model No. PRPOS-24-DR

Prestige Underbar Point Of Service Cabinet, 24"W x 25"D x 36"H, 25" working height, 18 gauge 300 series stainless steel flat top with 2" access hole for electrical cables, 12"H backsplash, louvered door with flush handle, 20 gauge 300 series stainless steel construction, 18 gauge 300 series stainless steel legs with adjustable stainless steel bullet feet, NSF

-
- 7 1 ea **(10) BEER & (2) WINE TAPS & DRAINER - WALL MOUNTED**
 Daniels Company Model No. CUSTOM
 (10) Beer & (2) Wine Taps & Drainer - Wall Mounted
- 2 ea **12-Faucet Air-Cooled Kronos Tower w/Stainless Steel Faucets - Drainer**
 Wall Mounted
- 2 ea **4-Way Regulator Panel w/F.O.B.'s and Stainless Steel Keg Couplers**
- 2 ea **1-Way Regulator Panel w/F.O.B.'s and Stainless Steel Keg Couplers**
- 1 ea **2-Way Regulator Panel w/F.O.B.'s and Stainless Steel Keg Couplers**
- 2 ea **Blower, 29 CFM (ES-29-2A)**
- 30 ea **1" Blower Hose**
- 200 ea **3/8" Vinyl Tubing**
- 250 ea **3/16" Vinyl Tubing**
- 1 ea **McDantim Blender w/Primary Regulators**
- 1 ea **Install Kit (Tape, Clamps, Fittings, etc.)**
-

- 4 ea **TRASH RECEPTACLE, INDOOR**
 Rubbermaid Commercial Products Model No. FG354060GRAY
 Packed 4 ea
 Slim Jim® Container, 23 gallon, 22"W x 11"D x 30"H, with venting
 channels, molded-in handles, general purpose waste, open type
 without lid, high-impact plastic construction, gray, Made in USA
-

- 3 ea **ICE BIN**
 Advance Tabco Model No. PRI-24-30-10
 Prestige Ice Chest, 30" wide, with 10-circuit cold plate, stainless steel
 construction with foam insulation, 7" backsplash, 1/2" drain, 25"
 front-to-back, 11" deep bin, 89 lbs ice capacity, soda chase provision
 in top of backsplash
- 3 ea **PRSH-24-6 Prestige Soda Gun Holder**, 6"W x 25"D, manifold housing
 for soda lines with removable cover, includes backsplash, stainless
 steel construction, NSF
- 3 ea **PRA-SSC-30 Prestige Sliding Cover**, 29-1/2"W x 16-1/2"D, for 30"W ice
 bin, 20/300 series stainless steel (for 30" pass thru ice bins see
 PRASSC-PT30)
-

- 3 ea **DRAINBOARD**
 Advance Tabco Model No. PRSCO-19-24-M
 Prestige Underbar Drainboard Cabinet, open front, 24"W x 25"D x
 36"H, 7" backsplash, removable perforated drainboard top, drain
 pan with 1" drain, (1) adjustable mid-shelf in cabinet, stainless steel
 construction, adjustable stainless steel bullet feet, NSF
-

2 ea HAND SINK

Advance Tabco Model No. PRHSST-19-12

Prestige Hand Sink, underbar, 12"W x 20"D x 36"H (overall), 9" wide x 9" front-to-back x 4" deep bowl, splash mount faucet with 6" spout, 7"H backsplash, deck mounted soap dispenser, c-fold towel dispenser, stainless steel construction, adjustable bullet feet, NSF

2 ea SU-20RL Prestige side splash, welded, both ends, for 20" deep unit (factory install only)

1 ea UNDERBAR SINK UNITS

Advance Tabco Model No. PRB-24-22C

Prestige Underbar Sink Unit, 2-compartment, 24"W x 25"D x 36"H, 14" front-to-back x 10" left-to-right x 10" deep sink bowls, no drainboards, 7"H backsplash, stainless steel open frame base, side crossrails, stainless steel construction, includes: (1) deck mount faucet with 6" swing spout, NSF

1 ea DRAINBOARD

Advance Tabco Model No. PRD-24-12

Prestige Underbar Drainboard, free-standing, 12"W x 25"D x 36"H, 7"H

backsplash, 18 gauge perforated removable drainboard top, 1"IPS drain, 20 gauge stainless steel construction, 18 gauge stainless steel legs with adjustable stainless steel cross-bracing & adjustable stainless steel bullet feet, NSF

1 ea S/S PERFORATED DRAINER PAN

Pro Stainless Inc. Model No. CUSTOM

S/S Perforated Drainer Pan

1 ea DROP-IN ICE BIN

Advance Tabco Model No. FAB-X4

Ice Bin, drop-in, 62-lb ice capacity, 26"W x 19-1/2"D x 14" deep overall (bin size 24"W x 13-1/2"D x 11" deep), built-in 7-circuit cold plate, removable stainless steel sliding cover, insulated, 1/2" diameter drain, NSF (cutout size 15-1/4" x 26-3/8")

1 ea SU-13 Upgrade (7) circuit cold plate to (10) circuit cold plate (factory install only)

1 ea S/S PERFORATED DRAINER PAN

Pro Stainless Inc. Model No. CUSTOM

S/S Perforated Drainer Pan

1 ea GLASS FILLER

T&S Brass Model No. 5GF-8P

Equip Glass Filler, 8" deck mount pedestal, 1/2" NPT male shank

1 ea UNDERBAR SINK UNITS

Advance Tabco Model No. PRB-24-53C

Prestige Underbar Sink Unit, 3-compartment, 60"W x 25"D x 36"H, 14" front-to-back x 10" left-to-right x 10" deep sink bowls, 12" drainboards on left & right, 7"H backsplash, stainless steel open frame base, side crossrails, stainless steel construction, includes: (1) deck mount faucet with 12" swing spout, NSF

1 ea BACK BAR CABINET, REFRIGERATED

Hoshizaki Model No. BB80-S

Refrigerated Back Bar Cooler, reach-in, three-section, side mount selfcontained refrigeration, 80"W, 28.74 cu. ft. capacity, holds approximately (1092) 12 oz. cans or (4) 1/2 Kegs, (3) solid hinged doors (locking), (6) adjustable shelves, LED interior lighting, 18 gauge stainless steel top, stainless steel interior & exterior front sides & rear, R290 Hydrocarbon refrigerant, 1/3 HP, 115v/60/1-ph, 2.5 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts on compressor

1 ea 8-FAUCET TOWER

Daniels Company Model No. CUSTOM

8-Faucet Tower - Direct Draw

1 ea 8-Faucet Tower - Direct Draw

1 ea Drain Pan, 24" x 7"

8 ea Domestic keg coupler

2 ea 4-Way air manifold

1 ea Install Kit (tape, clamps, fittings, etc.)

1 ea FROZEN DRINK MACHINE, NON-CARBONATED, BOWL TYPE

Stoelting Model No. SCBF128-37

Frozen Beverage/Granita Countertop Dispenser, countertop, 15-3/5"W x 18-9/10"D x 27-9/10"H, (2) 10-liter bowls, magnetic drive and brushless motor system, digital controls, built-in timer, gasket-less spigot, standard double-wall bowls, 2100 BTU/hr compressor, 115v/60/1-ph, 10 amps, NEMA 5-15P, cETLus, NSF

1 ea 1 year parts & labor warranty, standard (North America Only)

1 ea 5 year warranty on compressor, evaporator/hopper assembly, drive motor, speed reducer, auger shaft & auger flights (against breakage) standard

1 ea SOILDED DISHTABLE W/SINK

Pro Stainless Inc. Model No. CUSTOM

Soilded Dishtable w/Sink

- 1 ea T&S Brass B-0133-B EasyInstall Pre-Rinse Unit**, wall mount. base faucet with spring check cart. & lever handles, 2" dia. flanges with 1/2" NPT female eccentric flanged inlets, 35-1/2"H, 15" overhang, 8-1/4" clearance, 18" riser, (B-0107) spray valve, B-0044-H flex stainless steel hose, 6" wall bracket, quarter-turn Eterna cartridges, low lead

1 ea DOUBLE SIDED RACK SHELF

Pro Stainless Inc. Model No. CUSTOM

Double Sided Rack Shelf

1 ea CONDENSATE HOOD

Captive-Aire Model No. 4824VHB-G

Condensate Hood - 4ft 0" Long Condensate Hood, w/ Full Perimeter Gutter

- 430 SS - 100% Application

- EXHAUST RISER - Factory installed 10" Diameter X 4" Height

AS PER CAPTIVE AIRE QUOTE #4653835 DATED 12-28-20

- 1 ea DU33HFA High Speed Direct Drive Centrifugal Upblast Exhaust Fan** with speed control (speed control included for single phase only), disconnect switch and 11-3/4" wheel.
Exhaust Fan handles 600 CFM @ -0.500" wc ESP, Fan runs at 1242 RPM.
Exhaust Motor: 0.333 HP, 1 Phs, 115 V, 60Hz, 4.3 FLA, TEAO-ECM (Totally Enclosed Air Over Electronically Commutated Motor)
- ECM Wiring Package and Manual or 0-10VDC Control for Exhasut EC motors. MSC Controller. **DO NOT ORDER UNDER WARRANTY, SEE PART NUMBER "CAS MSC**.
- 1 ea** - Dish EF (31) Curb CRB19.5X18E On Fan #1 4.000:12.000 Pitch VERIFY
Singer Ashland Enclosure Panels

1 ea FLOOR TROUGH

IMC/Teddy Model No. FWR-96-SG

FWR Floor Water Receptacle, 96"W x 7-1/2"D, 4" deep receptacle, (1) 4" OD tailpiece, stainless steel beehive strainer, 16/304 stainless steel construction, brushed satin finish, (SG) subway grating, NSF, Made in USA

1 ea (3) COMPARTMENT SINK / CLEAN DISHTABLE

Pro Stainless Inc. Model No. CUSTOM

(3) Compartment Sink / Clean Dishtable

- 1 ea **T&S Brass B-0231-CC Sink Mixing Faucet**, 12" swing nozzle, wall mounted, 8" centers on sink faucet with 1/2" IPS CC male inlets, lever handles, quarter-turn Eterna cartridges, low lead, ADA

- 1 ea **Compliant T&S Brass B-0133-01 EasyInstall Pre-Rinse Unit**, mixing faucet, 8" wall mount, 14" add-on 063X swing nozzle, 18" riser, overhead spring, lever handles, 56" flex hose, Eterna cartridges, spray valve (B-0107), 9" wall

- 3 ea **support (B-0109-02), 1/2" male NPT**, EPA2005 Compliant T&S Brass B-3950-01 Waste Valve, twist handle, 3-1/2" sink opening, 2" drain outlet with 1-1/2" adapter & overflow assembly (replaces B3916-01)

1 ea WALL SHELF W/POT RACK

Pro Stainless Inc. Model No. CUSTOM

Wall Shelf w/Pot Rack

2 ea HAND SINK

John Boos Model No. PBHS-W-0909-P-SSLR-X

Pro-Bowl Hand Sink, wall mount, 12"W x 14-1/2"D x 12-1/4"H

overall size, 9"W x 9" front-to-back x 5" deep bowl, splash mount faucet holes with 4" centers, 2" drain opening with basket drain, with left & right side splash, all stainless steel construction, includes mounting bracket, NSF, CSA-Sanitation (splash mount faucet included)

- 2 ea (Available in Effingham)

Standard flyer accessories only, NO modifications to flyer items allowed or their accessories

1 ea WORK TABLE, 72", STAINLESS STEEL TOP

John Boos Model No. ST4R5-3072SSK

Work Table, 72"W x 30"D, 14/300 stainless steel top with 5" backsplash, with Stallion Safety Edge front, 90° turndown on sides, stainless steel legs & adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation, KD

2 ea X-0413H Mitered Edge, front corner of table top (modification)

1 ea CUT1618144 Weld-In Undermount Sink, 1-compartment, 16"W x 18" front-to-back x 14" deep, 3-1/2" drain opening, 14/300 stainless steel fabricated bowl, includes cutout, bowl, faucet holes & welding/polishing (Not available for FBLG & UFBLG)

1 ea X-0205B On the right (modification)

1 ea PB-LWB Lever waste support arm bracket. Not for use with PB-LWS-1 or PB-LWS-10V straight handle lever waste.

1 ea Note: Provisions made at factory for installation.

1 ea X-0414C Over flow hole, rear centered (modification)

1 ea T&S Brass B-0221-CC Mixing Faucet, deck mount, 12" swing nozzle, 8" centers on deck faucet with 1/2" IPS CC male inlets, quarter-turn Eterna cartridges with spring checks, lever handles, low lead, ADA Compliant

1 ea T&S Brass B-3950-01 Waste Valve, twist handle, 3-1/2" sink opening, 2" drain outlet with 1-1/2" adapter & overflow assembly (replaces B3916-01)

2 ea SHELVING, WALL MOUNTED

John Boos Model No. BHS1272-16/304

Shelf, wall-mounted, 72"W x 12"D x 9-1/2"H overall size, 1-1/2" rear up-turn, Stallion Safety Edge front, 16/300 stainless steel, NSF, KD

1 ea SOLID SHELVING

Metro Model No. 1860FS

Super Erecta® Shelf, solid, 60"W x 18"D, stainless steel, flat, raised "ship's edge" on all (4) sides, aluminum castings lock corners to posts

2 ea 1860NC Super Erecta® Shelf, wire, 60"W x 18"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

3 ea 1848FS Super Erecta® Shelf, solid, 48"W x 18"D, stainless steel, flat, raised "ship's edge" on all (4) sides, aluminum castings lock corners to posts

6 ea 1848NC Super Erecta® Shelf, wire, 48"W x 18"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

16 ea 33P Super Erecta® SiteSelect™ Post, 34-3/8"H, adjustable leveling bolt, posts are grooved at 1" increments & numbered at 2" increments, double grooved every 8", chrome finish

1 ea DOUBLE OVERSHELF - CEILING HUNG

Pro Stainless Inc. Model No. CUSTOM

Double Overshelf - Ceiling Hung

2 ea HEAT LAMP

Hatco Model No. GRAHL-48D3

Glo-Ray® Infrared Foodwarmer, 48" W, high wattage, tubular metal heater rod with lights, double heater rod housing 3" spacing, aluminum construction, 2440 watts, NSF, cULus, Made in

1 ea USA

NOTE: Sale of this product must comply with Hatco's Minimum Resale

1 ea Price Policy; consult order acknowledgement for details

2 ea NOTE: Includes 24/7 parts & service assistance, call 800-558-0607

One year on-site parts & labor warranty, plus one additional year parts

2 ea only warranty on all Glo-Ray metal sheathed elements

2 ea 120v/60/1-ph

REM INF 2 (2) Remote infinite control in lieu of standard built-in toggle, shipped loose (max. 12.2 amp each) INCLUDES THE

2 ea STANDARD TOGGLE FOR LAMP CONTROL price for two (available at time of purchase only)

IND.LGT-2-REM (2) Indicator Lights (Remote only) (available at time of purchase only) per circuit (remote control only on all tandem element

2 ea units)

STANDARD Clear Anodized Aluminum housing, finish, standard (available at time of purchase only)

1 ea S/S WORK TABLE

Pro Stainless Inc. Model No. CUSTOM

S/S Work Table

1 ea WARMING DRAWER, FREE STANDING

Hatco Model No. HDW-3N

Warming Drawer Unit, Free Standing, narrow, three drawers, includes

(1) standard 6" deep food pan per drawer, stainless steel construction, thermostatic controls, 4" legs, CE, cULus, NSF, Made in USA

1 ea NOTE: Includes 24/7 parts & service assistance, call 800-558-0607

1 ea 2-Yr Warranty on drawer warmer heating elements against burnout, standard

1 ea 2-Yr Warranty on drawer slides & rollers against breakage, standard

1 ea STANDARD Stainless Steel Drawer Front, standard (available at time of purchase only)

1 st HDW-CASTER-3 Casters, 3" diameter, locking (adds 4-1/4" to height of unit)

1 ea HOT FOOD SERVING COUNTER / TABLE

Delfield Model No. EHEI36C

E-Chef™ Hot Food Table, Electric, 36" L, (2) 12" x 20" sealed hot food wells with drains, infinite controls, fill faucet (field installation includes pre-punched faucet holes (left & right) and (2) chrome plugs), 8" poly cutting board, open base, stainless steel plate shelf, top, sides, bottom shelf with 3" rear riser, casters, cUL, UL, NSF

1 ea 0460000N 1 year parts & labor warranty, standard

1 ea 120v/60/1-ph, 17.0 amps, NEMA 5-30P, standard

1 ea PIZZA PREPARATION REFRIGERATOR

Hoshizaki Model No. PR67A-D4

Steelheart Series Pizza Prep Table, two-section, 19.9 cu. ft., (9) 1/3 pan rail capacity (pans & adapter bars included), (4) drawers each accommodate (2) 12" x 20" x 6" deep pans (pans by others), 1/2" thick white polyethylene cutting board, stainless steel exterior front, sides & top, stainless steel interior, self-contained refrigeration, R290

Hydrocarbon refrigerant, 1/3 HP, cord, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts on compressor

1 ea 115v/60/1-ph, 6.0 amps, standard

1 ea Casters, 6" (set of 4), (2 with brakes), standard

1 ea WORK TABLE, STAINLESS STEEL TOP

John Boos Model No. ST6R1.5-1224SSK

Work Table, 12"W x 24"D, 16/300 stainless steel top with 1-1/2"H rear up-turn, with Stallion Safety Edge front, 90° turndown on sides, stainless steel legs & adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation, KD

1 ea PIZZA PREPARATION REFRIGERATOR

Hoshizaki Model No. PR46A-D2

Steelheart Series Pizza Prep Table, one-section, 11.0 cu. ft., (6) 1/3 pan rail capacity (pans & adapter bars included), (2) drawers each accommodate (2) 12" x 20" x 6" deep pans (pans by others), 1/2" thick white polyethylene cutting board, stainless steel exterior front, sides & top, stainless steel interior, self-contained refrigeration, R290

Hydrocarbon refrigerant, 1/3 HP, cord, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts on compressor

1 ea Casters, 6" (set of 4), (2 with brakes), standard

1 ea WORK TABLE, STAINLESS STEEL TOP

John Boos Model No. EFT8-3612SSK-X

Filler Table, 12"W x 36"D x 36-1/4"H overall size, 18/400 stainless steel top with 1-1/2" backsplash, Stallion Safety Edge front, 90° turndown on sides, stainless steel legs & adjustable undershelf, plastic bullet feet,

NSF, KD (Available in Effingham and Nevada)

1 ea REACH-IN FREEZER

Hoshizaki Model No. F2A-FS

Steelheart Series Freezer, reach-in, two-section, 50.37 cu. ft., top mounted self-contained refrigeration system, (6) epoxy-coated wire shelves, (2) full-height solid hinged doors, digital temperature display/controls, audible/visual alarms, LED interior lighting, stainless steel interior, stainless steel exterior front & sides, (4) 4" heavy duty casters (2 with brakes), R290 Hydrocarbon refrigerant, 1 HP, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts on compressor

1 ea 115v/60/1-ph, 8.7 amps, standard

2 pk HS-5052 Shelf, 21-1/4" x 26", epoxy coated wire, (1) pack, for 1, 2 or 3 section reach-in refrigerated units

1 st Casters, 4" (set of 4), standard

1 ea EXHAUST HOOD AND ALL ACCESSORIES

Captive-Aire Model No. 5424ND-2-PSP-F

Exhaust Hood (Left) - 7ft 6" Long Exhaust-Only Wall Canopy Hood with 18" Wide Front Perforated Supply Plenum with Built-in 3" Back

Standoff

- 430 SS Where Exposed
- Fire Cabinet on the Left Side 12.00" Width x 54" Length x 24.00" Height (Additional charges may apply for cabinet if not sold with fire system)
- FILTER - 20" tall x 16" (19.625" by 15.625") wide Stainless Steel Captrate Solo filter with hook, ETL Listed. Particulate capture efficiency: 85% efficient at 9 microns, 76% efficient at 5 microns. Used on hoods shipped AFTER 7/27/17.
- L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture)
- Extra Fixtures- L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture)
- Screw In Compact Fluorescent Bulb, L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe
- EXHAUST RISER - Factory installed 14" Diameter X 4" Height
- SUPPLY RISER - 12"x 28" Supply Riser with Volume Dampers - 1/2 Pint Grease Cup New Style, Flanged Slotted
- Electrical Package Installation in Utility Cabinet by Plant.
- BACKSPLASH 80.00" High X 198.00" Long 430 SS Vertical (Includes End Caps & Divider Bars)
- LEFT QUARTER END PANEL 23" Top Width, 0" Bottom Width, 23" High 430 SS
- Parts required to mount riser sensor on riser with 3 inch insulation double wall duct.

Exhaust Hood (Right)- 8ft 0" Long Exhaust-Only Wall Canopy Hood with

18" Wide Front Perforated Supply Plenum with Built-in 3" Back Standoff

- 430 SS Where Exposed
- FILTER - 20" tall x 16" (19.625" by 15.625") wide Stainless Steel Captrate Solo filter with hook, ETL Listed. Particulate capture efficiency: 85% efficient at 9 microns, 76% efficient at 5 microns. Used on hoods shipped AFTER 7/27/17.
- L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture)
- Extra Fixtures- L55 Series E26 Canopy Light Fixture - High Temp

Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture)

- Screw In Compact Fluorescent Bulb, L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe

- EXHAUST RISER - Factory installed 14" Diameter X 4" Height

- SUPPLY RISER - 12"x 28" Supply Riser with Volume Dampers

- 1/2 Pint Grease Cup New Style, Flanged Slotted

- Parts required to mount riser sensor on riser with 3 inch insulation double wall duct.

- RIGHT VERTICAL END PANEL 27" Top Width, 21" Bottom Width, 80" High Insulated 430 SS

As Per Captive Aire Quote #4653835 Dated 12/28/20

1 ea ANSUL-3.0/3.0 Ansul 6 gallon Fire System in Utility Cabinet (includes pre-piped hood(s) with detection, tank(s), release mechanism, microswitches and pull station). Includes piping for hoods: 2, 3.

1 ea DU180HFA High Speed Direct Drive Centrifugal Upblast Exhaust Fan with, disconnect switch and 18-3/4" wheel.

Exhaust Fan handles 1875 CFM @ -1.150" wc ESP, Fan runs at 1032 RPM. Exhaust Motor: 1.000 HP, 3 Phs, 208 V, 60Hz, 3.8 FLA, ODP, Premium (EPlus3) Eff.

- Grease Cup for kitchen-duty centrifugal exhaust fans,

Box Dimensions 17-1/8 L X 5-1/16 W X 3-3/4 H (20 GA.) (Includes Down Spout)

- Hinged Base for Curb. Standard Hinge attached to curb. Used on Fans with wheels 20 inches or smaller. 12 GA Galvanized.

- Vented Base for Curb

- Full Bottom Curb Corner. Base flange corners fully welded or staked by factory.

- KEF1 (52) Curb CRB26.5x20E On Fan #2 4.000:12.000 Pitch VERIFY

1 ea DU180HFA High Speed Direct Drive Centrifugal Upblast Exhaust Fan with, disconnect switch and 18-3/4" wheel.

Exhaust Fan handles 2000 CFM @ -1.150" wc ESP, Fan runs at 1045 RPM. Exhaust Motor: 1.500 HP, 3 Phs, 208 V, 60Hz, 6.6 FLA, ODP, Premium (EPlus3) Eff.

- Grease Cup for kitchen-duty centrifugal exhaust fans,

Box Dimensions 17-1/8 L X 5-1/16 W X 3-3/4 H (20 GA.) (Includes Down Spout)

- Hinged Base for Curb. Standard Hinge attached to curb. Used on Fans with wheels 20 inches or smaller. 12 GA Galvanized.
- Vented Base for Curb
- Full Bottom Curb Corner. Base flange corners fully welded or staked by factory.
- KEF2 (52) Curb CRB26.5x20E On Fan #3 4.000:12.000 Pitch VERIFY

1 ea A2-D.250-20D Direct Gas Fired Heated Make Up Air Unit with 20" Direct

Drive Fan

Supply Fan handles 3100 CFM @ 0.450" wc ESP, Fan runs at 1233 RPM.

Heater supplies 172098 BTUs. 52°F Temperature Rise. [Fuel: Natural Gas]

Supply Motor: 2.000 HP, 3 Phase, 208 V, 60Hz, 6.1 FLA, ODP, Premium (E-Plus3) Eff.

Down Discharge - Air Flow Right -> Left

- Sloped Filtered Intake for Size #2 Modular Heater.

26.813" Wide X 53.625" Long X 31.313" High.

Includes 2" MV EZ Kleen Metal Mesh Filters.

- Profile Plate Configuration for size 2 Direct Fired Unit for low cfm applications.

- Separate 120VAC Wiring Package for Make-Up Air Units. Option must be selected when mounting VFD in prewire panel or with DCV package. Provides separate 120VAC input to supply fan. This 120V signal must be run by electrician from DCV to mua switch. - Gas Pressure Gauge, -5 to +15 Inches Wc., 2.5" Diameter, 1/4" Thread Size

- Gas Pressure Gauge, 0-35", 2.5" Diameter, 1/4" Thread Size - Low Fire Start. Allows the burner circuit to energize when the modulation control is in a low fire position.

- Motorized Back Draft Damper 22.75" X 24" for Size 2 Standard & Modular Heater Units w/Extended Shaft, Standard Galvanized Construction, 3/4" Rear Flange, Low Leakage, LF120S Actuator Included - Cooling Interlock Relay. 24VAC Coil. 120V Contacts. Locks out burner circuit when AC is energized.

- Gas Manifold for DF2 GM - BTU 0 - 825001 - 7 in. w.c. - 14 in. w.c., No

Insurance Requirement (ANSI), BV250-88

- RTC Solutions • 40-90°F Discharge Temp Control

- Full Bottom Curb Corner. Base flange corners fully welded or staked by factory.
 - KMUA (52) Curb CRB31X79X15INS Insulated On Fan #4 4.000:12.000 Pitch - Parallel to the Roof
- 1 ea DCV-2111 Demand Control Ventilation, w/ control for 2 Exhaust Fans, 1 Supply Fan, Exhaust on in Fire, Lights out in Fire, Fans modulate based on duct temperature. INVERTER DUTY 3 PHASE MOTOR REQUIRED FOR USE WITH VFD. Room temperature sensor shipped loose for field installation. Verify distance between VFD and Motor; additional cost could apply if distance exceeds 50 feet. Includes 2 Duct Thermostat kits.
- Thermistor CABLE - 18/2 AWG GREEN WHITE, plenum rated. USED for thermistor duct stat. Per Foot Price.
 - Digital Prewire Lighting Relay Kit. Includes hood lighting relay & terminal blocks. Allows for up to 1400W of lighting each. - VERIZON CELLULAR KIT, WIRED ANTENNA AND VERIZON DATA FOR 1 YEARS.
 - ESV751N02YXB571 - Variable Frequency Drive - 1 HP Max., 200/240 V,
Single or Three Phase Input, 4.2 A Max., NEMA 1 Enclosure, with 2RJ-45
FOR MODBUS
 - ESV152N02YXB571 - Variable Frequency Drive - 2 HP Max., 200/240 V,

Item	Qty	Description	Sell	Sell Total
		Single or Three Phase Input, 7.0 A Max., NEMA 1 Enclosure, with 2RJ-45 FOR MODBUS		
		- ESV152N02YXB571 - Variable Frequency Drive - 2 HP Max., 200/240 V, Single or Three Phase Input, 7.0 A Max., NEMA 1 Enclosure, with 2RJ-45 FOR MODBUS		
	1 ea	CASLink Monitoring		
<hr/>				
	1 ea	FIRE SUPPRESSION SYSTEM		
		Captive-Aire Model No. ANSUL		
		Fire Suppression System Hookup with certification, air test, 2" mechanical valve and \$200 permit fee allowance. Does not include pre-test, re-test, or room extinguisher:		
<hr/>				
	1 ea	CONVECTION OVEN, GAS		
		Blodgett Model No. ZEPH-100-G SGL		
		Zephaire Convection Oven, gas, single-deck, standard depth, capacity (5) 18" x 26" pans, (SSI-D) solid state infinite controls with digital timer, two speed fan, dependent glass doors, interior light, stainless steel front, sides and top, 25" stainless steel legs, 50,000		
	1 ea	BTU, ETL, NSF		
		2 year parts, 2 year labor and 1 additional year door warranty (parts		
	1 ea	only), standard		
	1 ea	Natural gas		
		115v/60/1-ph, 6.0 amps, 2-wire with ground, cord & plug, 1/2 hp,		
	1 ea	standard		
	1 ea	SSI-D Solid State infinite with digital timer, standard		
	1	st Venting to be determined		
	1 ea	25" legs, adjustable, stainless steel (set), standard		
	1 ea	6" stem casters		
	1 ea	NOTE: DO NOT deduct cost of standard legs		
		Dormont 1675BPQSR48 Dormont Blue Hose™ Moveable Gas Connector Hose Assembly, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) Snap'N Go, coiled restraining cable with hardware,		
		167,000 BTU/hr minimum flow capacity, limited lifetime warranty		
<hr/>				
	1 ea	CHEESEMELTER, GAS		
		Southbend Model No. P36-CM		

Platinum Heavy Duty Cheesemelter Match, gas, 36", riser mount, (4) infrared burners, (5) position rack guides, (1) chrome plated rack, dual

Item	Qty	Description	Sell	Sell Total
		valve control, 90 second preheat time, removable crumb tray, stainless steel construction, 40,000 BTU (Note: Qualifies for Southbend's Service First™ Program, see Service First document for details)		
	1 ea	Domestic Shipping, inside of North America		
	1 ea	Standard (1) year limited parts and labor warranty (reference warranty document for details)		
	1 ea	Natural Gas		
	1 ea	Stainless steel bottom sloped enclosure (required in some states)		
	1 ea	S/S WALL MOUNTING BRACKETS Pro Stainless Inc. Model No. CUSTOM S/S Wall Mounting Brackets		
	1 ea	EQUIPMENT STAND, REFRIGERATED BASE Hoshizaki Model No. CR85A Steelheart Series Refrigerated Equipment Stand, two-section, 85"W x 32-1/4"D x 27"H, (4) drawers: left two drawers will accommodate (3) 12" x 20" x 6" deep pans each, right two drawers will accommodate (2) 12" x 20" x 6" deep pans each (pans not included), solid state digital controller with temperature alarms, LED display, stainless steel front, sides, & top, stainless steel interior, side-mounted self-contained refrigeration, R290 Hydrocarbon refrigerant, 1/5 HP, 115v/60/1-ph, 3.0 amps, NEMA 5-15P, (6) 4" casters (all with brakes), cETLus, ETLSanitation		
	1 ea	Warranty: 3-Year parts & labor on entire machine		
	1 ea	Warranty: 5-Year parts on compressor		

1 ea HOTPLATE, COUNTERTOP, GAS

Star Model No. 606HF

Star-Max® Hotplate, countertop, gas, 36" wide, (6) cast iron burners, manual controls, heavy duty cast iron grates, drip tray, heavy duty knobs, stainless steel front with aluminized steel body, 4" adjustable legs, 150,000 BTU (ships Natural gas includes LP conversion kit), NSF, CSA, CGA

1 ea 2 year parts & labor warranty, standard

1 ea 180 day warranty on cast iron grates, burners, & burner shields, standard

1 ea Dormont 1675BPQSR48 Dormont Blue Hose™ Moveable Gas Connector Hose Assembly, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) Snap'N Go, coiled restraining cable with hardware, 167,000 BTU/hr minimum flow capacity, limited lifetime warranty

1 ea GAS COUNTERTOP GRIDDLE

Southbend Model No. HDG-48

Griddle, countertop, gas, 48" W x 24" D cooking surface, 1" thick polished steel plate, thermostatic controls, battery spark ignition,

flame failure safety device, stainless steel front, sides & 4" adjustable legs, 120,000 BTU, CSA, NSF (Note: Qualifies for Southbend's Service First™ Program, see Service First document for details)

1 ea Domestic Shipping, inside of North America

1 ea Standard one year limited warranty

1 ea Natural Gas

1 ea 400° thermostat control, standard

1 ea Dormont 1675BPQSR48 Dormont Blue Hose™ Moveable Gas Connector Hose Assembly, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) Snap'N Go, coiled restraining cable with hardware, 167,000 BTU/hr minimum flow capacity, limited lifetime warranty

3 ea GAS FLOOR FRYER

Pitco Frialator Model No. SG14-S

Solstice™ Fryer, gas, floor model, full frypot, 40-50 lb. oil capacity, millivolt control ONLY, includes drain line cleanout rod & drain extension, stainless steel tank, front, door & sides, 110,000 BTU, NSF, CE, CSA Flame, CSA Star, AuGA (free standing, stand alone only fryer special price)

3 ea 1 year parts and labor warranty from the date of installation up to a maximum of 15 months from the date of manufacture (with appropriate documentation), standard

1 ea Natural gas

3 ea P6072145 Basket, (2) oblong/twin size, 13-1/2" x 6-1/2" x 5-3/4" deep, long handle, regular mesh (shipped std (n/c) with models "T" SG14, SG14R, SSH55, SE14, SE14X, SE14B, SG14T, 35+, 45+, fryer batteries shipped with (1) per fryer

3 st B3901504 Casters, 9" adjustable swivel (set of 4) non-lock rear & lock front casters, solstice supreme, SG, SE, VF and flat bottom fryers, pasta cookers, rethermalizers, BNB

2 ea Connecting Strips N/C

3 ea Dormont 1675BPQSR48 Dormont Blue Hose™ Moveable Gas Connector Hose Assembly, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, (1) SnapFast® QD, (1) Swivel MAX®, (1) Snap'N Go, coiled restraining cable with hardware, 167,000 BTU/hr minimum flow capacity, limited lifetime warranty

1 ea S/S BOWL CABINET

Pro Stainless Inc. Model No. CUSTOM

S/S Bowl Cabinet

1 ea WORKTOP FREEZER

Hoshizaki Model No. WF27A

Steelheart Series Worktop Freezer, reach-in, one-section, 27"W, 7.21 cu. ft., self-contained rear mounted refrigeration system, (1) solid

hinged door, (1) adjustable shelf, stainless steel interior, stainless steel exterior front, sides & top, (4) 6" stem casters (2 with brakes), R290 Hydrocarbon refrigerant, 1/5 HP, NEMA 5-15P, cETLus, ETLSanitation, ENERGY STAR®

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts on compressor

1 ea 115v/60/1-ph, 2.5 amps, standard

10 ea WIRE SHELVING

Metro Model No. 2436NC

Super Erecta® Shelf, wire, 36"W x 24"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

10 ea 2430NC Super Erecta® Shelf, wire, 30"W x 24"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

10 ea 2448NC Super Erecta® Shelf, wire, 48"W x 24"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

10 ea 2454NC Super Erecta® Shelf, wire, 54"W x 24"D, chrome plated finish, plastic split sleeves are included in each carton, NSF

21 ea 86P Super Erecta® SiteSelect™ Post, 86-1/2"H, adjustable leveling bolt, posts are grooved at 1" increments & numbered at 2" increments, double grooved every 8", chrome finish

1 ea ICE BIN FOR ICE MACHINES

Hoshizaki Model No. B-500SF

Ice Bin, 30"W, top-hinged front-opening door, 500-lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, painted legs included, protected with H-GUARD Plus Antimicrobial Agent, ETL, ETL-Sanitation

1 ea Warranty: 3-Year parts & labor for bin

1 ea ICE MAKER, CUBE-STYLE

Hoshizaki Model No. KM-901MAJ

Ice Maker, Cube-Style, 30"W, air-cooled, self-contained condenser, production capacity up to 905 lb/24 hours at 70°/50° (753 lb AHRI certified at 90°/70°), crescent cube style, stainless steel exterior, R404A refrigerant, 208-230v/60/1-ph, 13.0 amps,

1 ea NSF, UL

1 ea Warranty: 3-Year parts & labor on entire machine

1 ea Warranty: 5-Year parts & labor on evaporator

Warranty: 5-Year parts on compressor & air-cooled condenser

1 ea WATER FILTRATION SYSTEM, FOR MULTIPLE APPLICATIONS

Everpure Model No. EV932805

High Flow CSR Triple-MC2 System, for combination coffee brewers, fountain, ice & steam, 27,000 gallon capacity, 5 gpm flow rate, 0.2 micron rating (3) MC2 cartridges, (1) SRX scale reduction feeder, (1) EC210 pre-filter, low pressure alarm, water shut-off, pressure gauges, flushing valve, low pressure alarm, 110v/60/1-ph

1 ea Note: This system requires (3) cartridges, (1) pre-filter & (1) scale reduction feeder.

1 ea MOP SINK

John Boos Model No. PBMS2016-6-X

Mop Sink, floor mounted, 24-5/8"W x 19-3/8"D x 10"H overall size, 20"W x 16" front-to-back x 6" deep compartment, 3-1/2" diameter drain, marine edge on front & sides, tile edge on rear, 16/300 stainless steel construction, NSF (Available in Effingham and Nevada)

1 ea T&S Brass B-0665-BSTR Service Sink Faucet, 8" centers, 2-3/8"

clearance from wall to center of faucet, 8-7/8" from wall to center of outlet, rough chrome-plated finish, vacuum breaker nozzle with 3/4" garden hose thread & pail hook, built in screwdriver stops

1 ea SHELVING, WALL MOUNTED

John Boos Model No. PB-MSS824-X

Utility Shelf, wall-mounted, 24"W x 8"D, Stallion Safety Edge front, 11/2" riser on sides & rear, includes hooks & (2) mop/broom holder with locking cam, 16/300 stainless steel, KD (Available in Effingham)

5 ea WIRE SHELVING

Metro Model No. 2442NK3

Super Erecta® Shelf, wire, 42"W x 24"D, Metroseal™ Green epoxycoated corrosion-resistant finish with Microban® antimicrobial protection, plastic split sleeves are included in each carton, NSF

5 ea 86PK3 Super Erecta® SiteSelect™ Post, 86-1/2"H, adjustable leveling bolt, posts are grooved at 1" increments & numbered at 2" increments, double grooved every 8", Metroseal 3 Green epoxy coated corrosionresistant finish with Microban® antimicrobial protection

WIRE SHELVING

Metro Model No. 2460NK3

Super Erecta® Shelf, wire, 60"W x 24"D, Metroseal™ Green epoxycoated corrosion-resistant finish with Microban® antimicrobial protection, plastic split sleeves are included in each carton, NSF

24 ea 74PK3 Super Erecta® SiteSelect™ Post, 74-1/2"H, adjustable leveling bolt, posts are grooved at 1" increments & numbered at 2" increments, double grooved every 8", Metroseal 3 Green epoxy coated corrosionresistant finish with Microban® antimicrobial protection

1 ea FENCING

New Age Model No. CUSTOM

Aluminum Security Fence: Security fence, "L" type, leg w/centered door 101" wide, other leg 121" wide, no door. Floor to ceiling is 86". Leg with door consists of two panels 31-1/2" wide, 84" high, center door, right hinge (36" wide between uprights, 78-1/2" high opening), over door bar, stainless hasp (accepts padlock), eight telescoping brackets, includes the "XH" option; the 121" leg consists of four panels 29-1/4" wide, 84" high, sixteen telescoping brackets (attach fence to floor and ceiling); stainless steel fasteners. Note that these fences attach to the floor and ceiling only, door swing is outward or away from the enclosure.
